

SM7.06 – 32 AMP TEMPORARY POWER DISTRIBUTION UNIT



Model: SM7.06 – 3 Phase Supply

APPLICATIONS

- Used for temporary power reticulation
- Construction industry
- Heavy industry
- Indoor/outdoor events
- Ports

CONSTRUCTION

- 6 x 15A sockets single phase 3P
- Supply – 32A 3 phase + N + E, 415VAC IEC 60309
- Interconnection – 32A 3 phase + N + E, 415VAC IEC 60309
- Frequency 50Hz
- RCD – 4 pole, 30mA, 40A 415VAC
- IP44/IP65
- Includes 10kA RCD and 10kA MCB as standard
- Specially blended polyethylene enclosure
- Meets AS/NZS 61439.4 requirements for assemblies for construction sites
- Dimensions – 517mm (L) x 280mm (H) x 268mm (W)

PRODUCT FEATURES

- 2 year limited warranty
- Stackable for storage and transportation
- 40mm ground clearance
- Third party tested
- Impact resistant robust enclosure for outdoor use
- Assembled with standard industrial sockets allowing hassle free replacement
- Customisation available on request
- Assembled with trade tested components
- Designed for NZ & AU conditions
- Anti-theft locking ring available on request

Product Code	Supply Power	Socket Outlets	Weight (kg)
SM7.06	32A, 3 phase + N + E, 415VAC IEC 60309	6 x 15A single phase 3P	8